

OTS Discrete Wire Cable Assemblies were designed with the largest wire gauge that connectors can accommodate to meet any prototype requirement on the market. Discrete Cables reduce engineering (mechanical and electrical) and purchasing time needed to qualify a cable. In addition, they are crimped in an automated press eliminating the risk of poor crimping during prototyping. These cables are great for prototyping all the way into mass production.



Pico-Clasp 1.00mm Pitch



Pico-Lock 1.00mm Pitch



Pico-EZmate 1.20mm Pitch



Micro-Lock Plus 1.25mm Pitch CLIK-Mate 1.25mm Pitch





PicoBlade 1.25mm Pitch



CLIK-Mate 1.50mm Pitch



Pico-Lock 1.50mm Pitch



Pico-SPOX 1.50mm Pitch



CLIK-Mate 2.00mm Pitch



DuraClik 2.00mm Pitch



EdgeLock 2.00mm Pitch



iGrid 2.00mm Pitch



MicroClasp 2.00mm Pitch



Micro-Lock Plus 2.00mm Pitch Micro-Latch 2.00 Pitch





Micro-One 2.00mm Pitch



Milli-Grid 2.00mm Pitch



Mini50 2.00mm Pitch



Pico-Lock 2.00mm Pitch



Mini-Lock 2.50mm Pitch



Nano-Fit 2.50mm Pitch



KK Plus 250



C-Grid III 2.54mm Pitch



KK 254 2.54mm Pitch



SL (Positive Latch) 2.54mm Pitch Micro-Fit 3.00mm Pitch



Ultra-Fit 3.50mm Pitch



KK and KK Plus 3.96mm Pitch Mini-Fit 4.20mm Pitch











Standard .093" 6.70mm Pitch



PowerWize 7.50mm Pitch



Mega-Fit 5.70mm Pitch



Super Sabre 7.50mm Pitch



Mini-Fit Sr. 10.00mm Pitch



MultiCat 7.40mm Pitch

SEALED DISCRETE WIRE CABLE ASSEMBLIES



Mizu-P25 (Mini-Type) 2.50mm Pitch



MX150 3.50mm Pitch



Squba 3.60mm Pitch



Squba 1.80mm Pitch

DISCRETE WIRE CABLE ASSEMBLIES

Product	Series No.	Pitch (mm)	Туре	Rows	Circuits	Length (mm)
Pico-Clasp	<u>15133</u>	1.00	R-R	Single	2 to 8	50, 100, 150, 300, 450, 600
Pico-Lock	<u>15131</u>	1.00	R-R	Single	2 and 4	50, 100, 150, 300, 450, 600
	<u>15132</u>	1.50			6 to 12	
	<u>219656</u>	2.00			2 to 6	50, 100, 150, 300, 600
	219657	2.00	R-S			
Micro-Lock Plus	<u>45111</u>	1.25	R-R	Single	2 to 6	50, 100, 150, 300, 450, 600
	<u>218101</u>	2.00			2 to 8	50, 100, 150, 300, 600
	218102				2 to 6	
Pico-EZmate	<u>36920</u>	1.20	R-R	Single	2 to 6	50, 100, 150, 300, 450, 600
CLIK-Mate	224091	1.25	R-R	Single	2 to 10	150, 300, 600
	224092		R-S			
	<u>15135</u>	1.50	R-R	Single	2 to 8	50, 100, 150, 300, 450, 600
	221958	2.00	R-R	Single	2 to 10	150, 300, 600
	221959		R-S			



Product	Series No.	Pitch (mm)	Туре	Rows	Circuits	Length (mm)
PicoBlade	<u>15134</u>	1.25	R-R	Single	2 to 8	50, 100, 150, 300, 450, 600
Pico-SPOX	218396	1.50	R-R	Single	2, 3, 4, 6, 8	50, 100, 150, 300, 600
PICO-SPOX	218397		R-S			
DuraClik	218322	2.00	R-R	Single	2, 3, 4 ,5, 6, 8, 10	150, 300, 600
	218323		R-S			
EdgeLock	216330	2.00	R-R	Single	2, 4, 6, 10	150, 300, 600
EugeLock	<u>216331</u>		R-S			
iGrid	221955	2.00	R-R	Cinala	10 to 16	150, 300, 600
IGHU	221956	2.00	R-S	Single		
MicroClasp	<u>15136</u>	2.00	R-R	Single	2 to 8	50, 100, 150, 300, 450, 600
Micro-Latch	219678	2.00	R-R	Single	2, 3, 4, 5, 6, 8, 10	50, 100, 150, 300, 600
Migra One	219652	2.00	R-R	Cinala	2 2 4 5 6 9	FO 100 1FO 200 COO
Micro-One	219653	2.00	R-S	Single	2, 3, 4, 5, 6, 8	50, 100, 150, 300, 600
	218509		R-R		4, 6, 8, 10	50, 100, 150, 300, 600
Milli-Grid	218510	2.00	R-S	Dual		
	224050		R-R		2, 4, 8	150, 300, 600
Mini50	224051	2.00	R-S	Single		
144 PL 050	224089	2.50	R-R	Single	2, 3, 4, 5, 6, 8	150, 300, 600
KK Plus 250	224090	2.50	R-S	Single	2, 3, 4, 5, 6, 8	150, 300, 600
Mini-Lock	<u>15137</u>	2.50	R-R		1 to 15	50, 100, 150, 300, 450, 600
	<u>45130</u>	2.50	R-R	Dual	2, 4, 6, 8	150, 300, 1000
Nano-Fit	145130		R-R	Single	3, 4, 5, 6 ,7, 8	75, 150, 300, 1000
	219658		R-R	Dual	8, 10, 12, 14, 16	150, 300, 600
C-Grid III	<u>219659</u>	2.54	R-S			
	<u>217796</u>		R-R	Single	2, 3, 4, 5, 6, 8, 10	150, 300, 600
KK 254	<u>217797</u>	2.54	R-S			
	<u>216270</u>		R-R	Single	2, 3, 4, 5, 6, 8	50, 100, 150, 300, 600
	216271		R-S			
SL (Positive Latch)	216272	2.54	P-P			
	216273		P-S			
Micro-Fit	245132	3.00		Dual	2,4, 6, 8,10	150, 300, 1000
	145132		R-R	_, , , , , , , ,	.55, 566, 1566	
	214770		.,.,	Single	2 to 6	75, 150, 300, 1000
	217465		R-R		2, 3, 4, 6, 8	150, 300, 600
Ultra-Fit	217466	3.00	R-S	Single	2, 3, 4, 0, 0	130, 330, 000
	21/400		11-3			



Product	Series No.	Pitch (mm)	Туре	Rows	Circuits	Length (mm)
KK and KK Plus	<u>219664</u>	3.96	R-R	Single	2, 3, 4, 5, 6, 8	75, 150, 300, 1000
	<u>219665</u>		R-S			
	36921		R-R			
	<u>145135</u>	4.20	R-R	Single	2, 3, 4, 5, 6	75, 150, 300, 1000
	215320		R-R		2, 3, 4, 5, 6	150, 300, 600
	<u>215321</u>		R-S			
	215322	4.20	P-P			
	215323		R-S			
	<u>215325</u>		R-R	Dual	2, 4, 6, 8, 10	
	<u>215326</u>		R-S	Dual	2, 4, 6, 8, 10	150, 300, 600
Mini-Fit	<u>215327</u>		P-P			
	215328		R-S			
	215330		R-R	Single	2 to 6	180, 500, 1000, 2000, 3000
	217159	4.20	R-S	Sirigle		
	218310		R-R	Dual	2 to 4	150, 300, 600
	218311		R-S			
	<u>245135</u>		R-R		2, 4, 6, 8, 10	500, 1000, 2000
	<u>45135</u>		R-R		2, 4, 6, 8	150, 300, 600
NA:-: Fix NA	224085	4.20	R-R	Decel	2.4.6.0.40	450, 200, 600
Mini-Fit Max	<u>224086</u>	4.20	R-S	Dual	2, 4, 6, 8, 10	150, 300, 600
Mega-Fit	45136	5.70	R-R	Dual	2, 4, 6, 8, 10, 12	150, 300, 500, 600, 1000, 2000
	<u>216290</u>		R-R	Single/Dual	1, 2, 3, 4, 6	150, 300, 600
Standard .093"	216291	6.70	R-S			
	216292		P-P			
	216293		P-S			
MultiCat	<u>45141</u>	7.40	R-R	Single	3, 4	300, 1000
	<u>45142</u>		P-P			
Super Sabre	216010	7.50	R-R	Single	2, 3, 4	150, 300, 600
	216011		R-S			
PowerWize	221960	7.50	R-R, R-S	Single	2	1000
Mini-Fit Sr	<u>36924</u>	10.00	R-R	Single	2, 3, 4	150, 300, 1000



OTS SEALED DISCRETE WIRE CABLE ASSEMBLIES

Product	Series No.	Pitch (mm)	Туре	Rows	Circuits	Length (mm)
Mizu-P25	215310	0.50	R-R	Single	2, 3, 4	150, 300, 600
	<u>215311</u>		R-S			
	215312	2.50	P-P			
	<u>215313</u>		P-S			
	216280		R-R	Single	2, 3, 4, 6	150, 300, 600
MX150	<u>216281</u>		R-S			
	216282		P-P			
	216283	0.50	P-S			
	216285	3.50	R-R	Dual		
	216286		R-S			
	216287		P-P			
	216288		P-S			
Squba	<u>45145</u>	4.00	P-P	Single	2, 4, 6, 8, 10	150, 300, 1000
	<u>45146</u>	1.80	P-P			
	216620	3.60	R-R		2, 3, 4	150, 300, 600
	<u>216621</u>		R-S			
	216622		P-P			
	216623		P-S			