

MM101

8 Channel MEMS High Voltage Driver



Product Overview

Description

The MM101 is an 8-channel low-voltage serial-to-high-voltage parallel converter with push-pull outputs and an internal charge pump converter. The device is designed for MEMS applications where high-voltage generation and driving capability are desired in a high integration form factor. The internal charge pump operates with a 5.0 V input source to generate a high-voltage source for the 8-channel output drivers.

The circuitry includes power-on-reset and power ON/OFF sequence control. The communication interface consists of two modes of operation: GPIO and SPI, selected with the input control MODE pin

Features


- Eight High-Voltage Push-Pull Output Channels
- Internal Charge Pump Voltage Converter
- Power-On-Reset (POR)
- Selectable Communication Interface (SPI, GPIO)
- Up to 33 MHz SPI Clock Speed
- V_{DD_IO} Supply allows I/O levels to range from 1.8 V to 5.0 V
- SPI can be daisy-chained
- Under Voltage Protection
- Fault Indicators (Latched SPI register bit and unlatched Open-Drain FLTB pin)
- Available in a 5x5mm QFN package, and WLCSP Flip Chip package

Applications

- Microelectromechanical Systems
- Displays
- High Voltage Driver Applications

Markets

- Load/DIB for Semiconductor Test
- RF Systems
- Test and Measurement



Electrical Specifications

Operating Characteristics

Absolute Maximum Ratings

Exceeding the maximum ratings as listed in [Table 1](#) may reduce the reliability of the device or cause permanent damage. Operation of the MM101 should be restricted to the limits indicated in the recommended operating conditions listed in [Table 2](#).

Electrostatic Discharge (ESD) Safeguards

The MM101 is a Class 1A ESD device. When handling the MM101, observe precautions as with any other ESD sensitive device. Do not exceed the voltage ratings specified in [Table 1](#).

Power Sequencing

Power-up Sequence

- Connect Ground
- Apply VDD, VDD_{IO} and VIN – no supply sequencing restrictions on VDD, VDD_{IO} and VIN.
- Apply VPP (if using external high voltage supply)
- Apply input control signals

Table 1. Absolute Maximum Ratings

Parameter	Symbol	Min	Max	Unit
DC Supply Voltage	V _{DD}	-0.3	3.6	V
I/O Supply Voltage	V _{DD_IO}	-0.3	5.5	V
Charge Pump Input	V _{IN}	-0.3	5.5	V
Charge Pump High Voltage Output	V _{PP}	-0.3	105	V
Logic Input Voltage	V _{DIN}	-0.3	V _{DD_IO} + 0.3	V
ESD rating of low voltage pins	—	—	2000	V HBM
ESD rating of V_{PP} & HV# pins	—	—	500	V HBM
Junction Temperature Range	T _J	-55	165	°C
Storage Temperature Range	T _{stg}	-55	165	°C

Table 2. Recommended Operating Conditions

Parameter	Symbol	Min	Max	Unit	Conditions
Charge Pump Power Supply	V _{IN}	4.5	5.5	V	
Low Voltage Digital Supply	V _{DD}	3.0	3.6	V	
Logic Reference Level	V _{DD_IO}	1.71	5.25	V	
High Voltage Supply	V _{PP}	10	100	V	If using external V _{PP} supply
Operating Temperature	T _A	-40	125	°C	Ambient

Electrical Characteristics

All specifications valid over full supply voltage and operating temperature range unless otherwise noted (Note 1). Operating with all analog and digital GND pins connected to system ground (0 V). VPP = 85 V, CPP = 4.7nF, unless otherwise specified.

Table 3. Power Supply Specifications

Parameter	Symbol	Note	Min	Typ	Max	Unit	Test Conditions
VIN Current (Dynamic)	I _{VIND}	1	—	1.5	2.5	mA	Charge pump ON, VPP = 85 V, I _{OUT} = 20 uA, outputs switching at 10 kHz, CL = 2pF per CH
VIN Quiescent Current	I _{VINQ}		—	1.25	2.0	mA	Charge pump ON, VPP = 85 V, I _{OUT} = 20 uA, all I/O static
VDD UVLO Rising Threshold	UVLO _{RISE}		2.77	—	2.95	V	
VDD UVLO Falling Threshold	UVLO _{FALL}		2.72	—	2.90	V	
Low Voltage Digital Current	I _{DD}	1	—	520	700	μA	SPI mode outputs switching at 10 kHz, OCS = 0, CL = 2pF per CH.
Low Voltage Digital Quiescent Current	I _{DDQ}		—	470	550	μA	Charge Pump OFF, all I/O static
Low Voltage Digital Sleep Mode Current	I _{DDSLEEP}		—	<1	10	μA	Charge pump OFF, Sleep Mode ON
I/O Logic Supply Current	I _{DD_IOQ}		—	<10	50	μA	Outputs switching at 10 kHz.

Table 4. Digital Interface AC and DC Specifications

Parameter	Symbol	Note	Min	Typ	Max	Unit	Test Conditions
Logic I/O Level High	I/O _{VH}		0.7 x V _{DD_IO}	—	V _{DD_IO}	V	
Logic I/O Level Low	I/O _{VL}		0	—	0.3 x V _{DD_IO}	V	
Logic I/O Hysteresis (SCK only)	I/O _{VH}		—	0.25	—	V	
Digital Input Capacitance (MM101-03ADA)	C _{IN}		—	2	5	pF	
SDO Load Capacitance	C _{SDO}	2,3	—	—	10	pF	
SDO Source Current @ V_{DD_IO}						V _{OUT} = 0.8 x V _{DD_IO}	
5.0 V	I _{SDOH}		180	290	—	mA	
3.3 V	I _{SDOH}		75	140	—	mA	
1.8 V	I _{SDOH}		20	35	—	mA	
SDO Sink Current @ V_{DD_IO}						V _{OUT} = 0.2 x V _{DD_IO}	
5.0 V	I _{SDOL}		140	260	—	mA	
3.3 V	I _{SDOL}		65	140	—	mA	
1.8 V	I _{SDOL}		20	40	—	mA	
SSB pull-up resistor (to V_{DD_IO})	R _{PU}	—	120	200	280	kΩ	SSB pull-up is only in SPI mode
Internal pull-down resistors	R _{PD}	5	120	200	280	kΩ	SSB pull-down is only in GPIO mode
CP_EN pin toggle low time	T _{TOGGLE}		500	—	—	ns	Minimum time CP_EN must be held low to restart the IC from fault condition
FLTB pin max sink current			65	140	—	mA	FLTB = GND V _{DD_IO} =3.3V

Table 5. Digital Interface Timing Specifications

Parameter	Symbol	Note	Min	Typ	Max	Unit	Test Conditions
SPI Clock Frequency	f_{SCK}		—	—	33	MHz	
SDI Valid to SCK Setup Time	t_{SU}		2	—		ns	
SDI Valid to SCK Hold Time	t_{HD}		5	—		ns	
SCK High Time	t_{HI}		15.5	—	—	ns	
SCK Low Time	t_{LO}		15.5	—	—	ns	
SSB Pulse Width	t_{CSH}		15	—	—	ns	
LSB SCK to SSB High	t_{CSHLD}		15	—	—	ns	
SSB Low to SCK High	t_{CSSU}		15	—	—	ns	
SDO Propagation Delay from SCK Falling Edge	t_{SDOH}		10	—	—	ns	$C_L = 10\text{pF}$
SDO Output Valid after SSB Low	t_{CSDO}		20	—	—	ns	
SSB Inactive to SDO High Impedance	t_{SDOZ}		—	—	10	ns	

Table 6. Charge Pump and Driver Specifications

Parameter	Symbol	Note	Min	Typ	Max	Unit	Test Conditions
High Voltage CP Output							
VOS = 0	V _{PP}		77	80	83	V	
VOS = 1	V _{PP}		87	90	93	V	
Maximum Charge Pump Output Current	I _{CP,MAX}		15	—	—	µA	V _{IN} = 4.5 V, V _{PP} = 85 V
Charge Pump Output Ripple	V _{RIPPLE}		—	—	10	mV _{p-p}	All HV Driver Outputs Off
Droop in V_{PP} voltage	V _{DROOP}		—	—	0.6	V	Droop in V _{PP} Voltage when 8 HV outputs toggle on, C _L = 3.5pF
Power-On-Reset	POR	2	—	<0.5	2.50	ms	Delay from application of VIN and VDD to all circuits active and stable
Charge Pump Start-Up Time	T _{ST}	4	—	8	33	ms	V _{IN} = 4.5 V, V _{PP} = 90 V, I _{OUT} = 20 µA, C _{PP} = 4.7nF
Driver Output Voltage High	HV _{OH}		V _{PP} -1	—	—	V	
Driver Output Voltage Low	HV _{OL}		—	—	1	V	
Driver Output Current							Per channel V _{PP} = 85 V
OCS = 0	I _{HV#}		24	30	36	µA	
OCS = 1	I _{HV#}		48	60	72	µA	
Output Enable Rising Threshold							Per channel V _{PP} = 85 V
VOS = 0	V _{EN}		65	69	71	V	
VOS = 1	V _{EN}		75	79	81	V	

Parameter	Symbol	Note	Min	Typ	Max	Unit	Test Conditions
Output Disable Falling Threshold							
VOS = 0	V_{DIS}		64	68	70	V	
VOS = 1	V_{DIS}		74	78	80	V	

Notes:

1. Specs are production tested at room temperature with temperature guard bands built into the limits unless otherwise noted
2. Specification is for design guidance only.
3. SDO load capacitance = PCB trace from SDO to input port (MM101 SDI or mC) + receiver CIN
4. From CP_EN pin or bit toggled high to VPP rises to 90% of set value.
5. The following pins have pull-down resistors: SDI, SCK, SSB, CP_EN, FLIP_BIT, OCS, and FLT_MODE.

Functional Block Diagram




Figure 1. Functional Block Diagram

32-Lead QFN Package Pinout




Figure 2. MM101 5 mm x 5 mm QFN Package Pinout (Top View/As Mounted)




Figure 3. MM101 2.37 mm x 1.58 mm Flip-Chip Package Pinout (Top View/As Mounted)

Table 7. Detailed Pin Description

QFN Pin #	Flip Chip Pin #	Name	Description
1-4, 6-9	2-9	HV#	High-voltage outputs.
5	14, 15	VPP	High-voltage input to the output drivers. Bypass with a 4.7 nF, 200 V, 10 % C0G ceramic capacitor.
10, 22	1, 20, 21	VDD	3.3 V supply to digital/analog circuits. Bypass with a low ESR 1 μ F ceramic capacitor.
11-14, 27, 29	32	NC	No connect, can optionally be connected to PCB ground.
15	17	CP_EN	Charge pump enable pin in GPIO mode. Pull-up to VDD_IO to enable the charge pump. Has a built-in pull-down resistor. Pin is ignored in SPI mode.
16	31	SCK/CTL1	Clock input in SPI mode; HV output control in GPIO mode. Has an internal pull-down resistor.
17	30	MOSI/CTL2	SPI data input in SPI mode; HV output control in GPIO mode. Has an internal pull-down resistor.
18	16	MISO/CTL3	SPI data output in SPI mode; HV output control in GPIO mode. Has an internal pull-down resistor.
19	29	SSB/CTL4	Chip select in SPI mode; HV output control in GPIO mode. Has an internal pull-up resistor to VDD_IO in SPI mode, and an internal pull-down resistor in GPIO mode.
20	28	MODE	Logic level input to switch inputs between SPI and GPIO modes. Connect to GND for SPI mode. Connect to VDD_IO for GPIO mode.
21	27	VDD_IO	For 3.3 V nominal digital I/O levels, connect to VDD. For alternate I/O levels, connect to a separate supply (+1.8V to +5.0V). Bypass with a low ESR 1 μ F ceramic capacitor if separate from VDD.
23	26	OCS	Output Current Select in GPIO mode. Connect to VDD_IO for high level or GND for low level. Has an internal pull-down resistor. Pin is ignored in SPI mode.
24	12, 13	FLIP_BIT	In GPIO mode FLIP_BIT controls the logic mapping between CTL1-4 and HV0-7. Refer to Table 8. Set high in SPI mode.
25	25	FLTB	Fault indicator in GPIO and SPI modes. Open drain output to allow "Wire-OR" of multiple ICs. Goes low when fault is detected. Can be left open if not used. Pull-up voltage must be \leq VDD_IO.
26	22	FLT_MODE	Fault Mode select in GPIO mode. Pull to VDD_IO to disable Fault Mode. Has a built-in pull-down resistor. Pin is ignored in SPI mode.

QFN Pin #	Flip Chip Pin #	Name	Description
28	23	VOS	Output voltage select in GPIO mode. Connect to VDD_IO for high level or GND for low level. Has a built-in pull-down resistor. Pin is ignored in SPI mode.
30	24	AGND	Analog ground, should be connected to PCB ground.
31	10	VIN	Connect to 5 V power supply. Bypass with a low ESR 1 μ F ceramic capacitor to CPGND.
32	11	CPGND	Charge pump ground, should be connected to PCB ground.
PAD	18, 19	DGND	Digital ground, should be connected to PCB ground.

Functional Description

The MM101 is an 8-Channel Low-Voltage Serial to High-Voltage Parallel Converter with Push-Pull Outputs and an Internal Charge Pump Converter. The device is designed for MEMS applications where high voltage generation and driving capability are desired in a high integration form factor.

The device consists of three main design blocks:

- Internal charge pump
- Communication interface
- 8 high-voltage push-pull drivers.

Charge Pump

The internal charge pump operates from a 5.0 V nominal input to generate the high voltage VPP for the HV Drivers. The output voltage can be selected to be either 90V or 80V using the VOS pin in GPIO mode or VOSET bit in SPI mode.

The VOS pin has a low current internal pull-down to GND. If the pin is left open or connected to GND, the output voltage defaults to 80 V. Pulling the pin to V_{DD_IO} sets the output high level to 90 V. Likewise, in SPI mode, if the VOSET register bit is zero, the output level (HV#) high levels are 80 V. If VOSET is set to 1, the HV# output levels are 90 V.

The charge pump is designed to simultaneously drive 8 High-Voltage Push-Pull Drivers with a total load capacitance of 10 pF. Multiple HV outputs can be tied together to increase the transient drive current, but the total load capacitance of all 8 HV outputs should be below 10 pF.

To measure the VPP or HV outputs accurately, a load greater than 20 $M\Omega$ (including probes or other test equipment) is required.

Supplying an External High Voltage

If it is desired to use an external voltage instead of the internal charge pump:

- VIN should be connected to CPGND.
- VPP should be applied 0.1 msec or more after VDD is applied.
- VOS pin should be set according to the VPP voltage that will be applied externally (80 V/ 90 V). This will ensure that the internal VPP under-voltage comparators function correctly.
- When using an external supply to drive VPP in GPIO mode, the status of the CP_EN pin affects VPP under voltage faults.

High Voltage Outputs

The eight, high-voltage outputs are powered from VPP and controlled by the digital inputs.

In SPI mode, the output current may be set to either the low level or high level by using the OCS register bit. The default state of OCS is a logic zero, which sets the output current level to low. In GPIO mode, the output current level is determined by the state of the OCS pin.

Programming

Communication Interface

The driver interface two modes of operation, Serial and GPIO (Parallel), selected by the MODE input pin.

Note: If MODE is toggled from GPIO to SPI, it is a good practice to pulse SSB low before the first 16-bit transaction. This will reset the SPI and ensure that it is ready to receive the first data packet.

All the SPI pins (except the SSB pin) the FLIP_BIT, and the MODE pin have an internal pull-down resistor to ensure that no digital input pins can float.

The SSB pin has a pull-up current source in SPI mode. This ensures that the IC defaults to a disabled state in SPI mode. In GPIO mode, this pin is CTL4. In this case, the CTL4 pin has a pull-down resistor. This ensures that the input is low by default in GPIO mode.




Figure 4. SPI Timing Diagram

Serial Communication

MODE = 0, activates the 16-Bit Serial Peripheral Interface (SPI) module for operation. Multiple devices can be daisy-chained to drive multiple ICs using one SPI bus. (See Daisy Chain Operation figures 7 to 9)

The SPI works at any frequency up to a maximum of 33 MHz and may operate at significantly lower frequencies if the logic signals adhere to the data setup and hold requirements.

SPI Interface Mode

SPI timing diagrams are provided in Figures 4 to 9. In SPI mode, data transmission starts when SSB goes Low, causing the Target to output the Most Significant Bit (MSB) of data to the SDO (MISO) pin. Data transfer from Host to Target takes place during the rising edge of the clock (SCK), which is idle when SSB is High. This mode of operation requires data for Host and Target to be present on SDI (MOSI) before the rising edge of the clock (defining SDI to SCK setup time). Data is pushed out of the SDO (MISO) pin during the falling edge of the clock. After the first 16-bit transaction, Host writes the latest data (DN) to Target, while Target passes its previous (DN-1) stored data to the Host. Data is latched into the internal registers at the rising edge of SSB, if WR_EN = 1.

SPI Data Format

SPI data is sent in a 16-bit format. The first MSB bit (WE), if high, enables the Write mode. The following 7 MSB bits hold the Control and Fault Status bits. The 8 LSB bits hold the Switch State bits




Figure 5. SPI Read Only (1 IC, No Daisy Chain)




Figure 6. SPI Read & Write (1 IC, No Daisy Chain)

SPI Control Registers

The SPI interface provides access to two 8-bit Internal Registers: Register STATE and Register CONTROL that are Read/Write registers. Register data is read by toggling SSB low and monitoring the data at the SDO pin while clocking the SCK pin. Register STATE holds the state of the 8 high-voltage outputs and is updated when SSB goes from LOW to HIGH, if the Write Enable bit is high.

Register CONTROL holds six control bits (OCSET, CPEN, VOSET, VPPCOMP, FLT_MODE, and SLEEP), and the fault status bit (FSTAT). The MSB bit enables the Write mode if high.

In SPI mode, the OCS, VOS, CP_EN, and FLT_MODE pins are ignored. Settings in the CONTROL register are used instead.

Note: The first row of the register tables below shows the read/write type, and default state. At power-on-reset (POR), all bits in both registers are set to LOW internally.

State Register

R/W - 0							
HV7	HV6	HV5	HV4	HV3	HV2	HV1	HV0
bit 7							bit 0

bit 7: HV7

1 = HV7 Output is Enabled (High)
0 = HV7 Output is Disabled (Low)

bit 6: HV6

1 = HV6 Output is Enabled (High)
0 = HV6 Output is Disabled (Low)

bit 5: **HV5**

1 = HV5 Output is Enabled (High)
0 = HV5 Output is Disabled (Low)

bit 4: HV4

1 = HV4 Output is Enabled (High)
0 = HV4 Output is Disabled (Low)

bit 3: HV3

1 = HV3 Output is Enabled (High)
0 = HV3 Output is Disabled (Low)

bit 2: HV2

1 = HV2 Output is Enabled (High)
0 = HV2 Output is Disabled (Low)

bit 1: HV1

1 = HV1 Output is Enabled (High)
0 = HV1 Output is Disabled (Low)

bit 0: **HVO**

1 = HV0 Output is Enabled (High)
0 = HV0 Output is Disabled (Low)

Control Register

R/W - 0							
WR_EN	FSTAT	SLEEP	FLTMODE	VPPCOMP	VOSET	CPEN	OCSET
bit7							

 bit 7: **WR_EN**

- 1 = Enable write mode
- 0 = Disable Write mode (read only)

 bit 6: **FSTAT** (see Note 1 below)

- 1 = VPP OR VDD Fault status = faulted
- 0 = VPP OR VDD Fault status = NOT faulted

 bit 5: **SLEEP** (see Note 2 below)

- 1 = SLEEP mode active (all analog circuits disabled)
- 0 = SLEEP mode inactive (all analog circuits enabled)

 bit 4: **FLTMODE**

- 1 = Fault Mode Disabled (shutdown disabled)
- 0 = Fault Mode Enabled (shutdown enabled)

 bit 3: **VPPCOMP**

- 1 = VPP under-voltage comparator is disabled
- 0 = VPP under-voltage comparator is active

 bit 2: **VOSET**

- 1 = VPP is set to 90 V
- 0 = VPP is set to 80 V

 bit 1: **CPEN**

- 1 = Charge Pump is enabled
- 0 = Charge Pump is disabled

 bit 0: **OCSET**

- 1 = Output current is set to 60 μ A
- 0 = Output current is set to 30 μ A

Notes:

1. VPP and VDD faults are latched. Once this bit is set high, it must be written to 0 to clear the fault.
2. The SLEEP bit is forced low in GPIO mode.

Daisy Chain Operation

Daisy chaining the ICs is permitted and involves connecting the SDO (MISO) of one chip to the SDIN (MOSI) of the next chip in the chain, as shown in [Figure 7](#). SPI timing diagrams with daisy-chained devices are provided in [Figure 8](#) and [Figure 9](#).




Figure 7. SPI with 2 ICs Daisy-chained




Figure 8. SPI Read Only (2 ICs Daisy-chained)




Figure 9. SPI Read and Write (2 ICs Daisy-chained)

Table 8. Switch State Table in GPIO Mode

Count	FLIP-BIT	Input Signals								HV					
		CTL4	CTL3	CTL2	CTL1	7	6	5	4	3	2	1	0		
0	1	0	0	0	0	OFF									
1	1	0	0	0	1	OFF	ON								
2	1	0	0	1	0	OFF	ON	OFF							
3	1	0	0	1	1	OFF	OFF	OFF	OFF	OFF	OFF	ON	OFF	OFF	
4	1	0	1	0	0	OFF	OFF	OFF	OFF	ON	OFF	OFF	OFF	OFF	
5	1	0	1	0	1	OFF	OFF	OFF	ON	OFF	OFF	OFF	OFF	OFF	
6	1	0	1	1	0	OFF	OFF	ON	OFF	OFF	OFF	OFF	OFF	OFF	
7	1	0	1	1	1	OFF	ON	OFF							
8	1	1	0	0	0	ON	OFF								
9	1	1	0	0	1	ON	OFF	ON	OFF	ON	OFF	OFF	ON	ON	
10	1	1	0	1	0	ON	OFF	ON	OFF	OFF	ON	ON	ON	OFF	
11	1	1	0	1	1	ON	OFF	OFF	ON	ON	OFF	ON	OFF	OFF	
12	1	1	1	0	0	OFF	ON	ON	OFF	ON	OFF	ON	OFF	OFF	
13	1	1	1	0	1	ON	OFF	ON	OFF	ON	OFF	ON	OFF	ON	
14	1	1	1	1	0	OFF	ON	OFF	ON	OFF	ON	OFF	ON	ON	
15	1	1	1	1	1	OFF									
16	0	0	0	0	0	OFF									
17	0	0	0	0	1	ON	OFF	ON							
18	0	0	0	1	0	OFF	ON	OFF	OFF	OFF	OFF	OFF	ON	OFF	
19	0	0	0	1	1	ON	ON	OFF	OFF	OFF	OFF	OFF	ON	ON	
20	0	0	1	0	0	OFF	OFF	ON	OFF	OFF	ON	OFF	OFF	OFF	

Count	Input Signals							HV						
	FLIP BIT	CTL4	CTL3	CTL2	CTL1	7	6	5	4	3	2	1	0	
21	0	0	1	0	1	ON	OFF	ON	OFF	OFF	ON	OFF	ON	
22	0	0	1	1	0	OFF	ON	ON	OFF	OFF	ON	ON	OFF	
23	0	0	1	1	1	ON	ON	ON	OFF	OFF	ON	ON	ON	
24	0	1	0	0	0	OFF	OFF	OFF	ON	ON	OFF	OFF	OFF	
25	0	1	0	0	1	ON	OFF	OFF	ON	ON	OFF	OFF	ON	
26	0	1	0	1	0	OFF	ON	OFF	ON	ON	OFF	ON	OFF	
27	0	1	0	1	1	ON	ON	OFF	ON	ON	OFF	ON	ON	
28	0	1	1	0	0	OFF	OFF	ON	ON	ON	ON	OFF	OFF	
29	0	1	1	0	1	ON	OFF	ON	ON	ON	ON	OFF	ON	
30	0	1	1	1	0	OFF	ON	ON	ON	ON	ON	ON	OFF	
31	0	1	1	1	1	ON								

Fault Conditions

There are two comparators that can signal a fault condition:

- VDD under voltage fault
- VPP under voltage fault

Note: The VPP under voltage comparator can be disabled. In SPI mode, it is disabled when the VPPCOMP bit in the CONTROL register is high. In GPIO mode, the comparator is disabled when CP_EN pin is set low.

Faults are reported differently depending on the mode of communication - SPI or GPIO. The outputs of the VDD and VPP fault comparators are logically OR'ed. The output of the OR gate controls the FLT_B pin. FLT_B is an open-drain output and is ON (low impedance) if either fault is detected. In SPI mode, bit 6 of the CONTROL register provides VDD and VPP fault status.

At start-up, the FLT_B pin is held OFF (high impedance). It is allowed to change state only after each voltage goes past its Enable threshold (VDD goes higher than UVLORISE and VPP goes higher than VEN). This prevents a race condition at startup.

Once VDD and VPP go above their thresholds, the comparators monitoring VDD and VPP actively monitor for faults. If VDD goes below UVLOFALL or VPP goes below VPPDIS, a fault condition is signaled by setting the FLT_B pin low and the Fault Status bit high (bit 6 in the CONTROL register). The FLT_B pin returns to an open state when the fault condition is cleared – the FSTAT bit remains latched high until it is cleared via a SPI write.

If Fault Mode is enabled (in GPIO mode, FLT_MODE pin = 0, in SPI mode, FLT_MODE bit = 0), the outputs are all set low and the charge pump is turned off. The user must toggle the CP_EN pin (GPIO mode) or the CPEN register bit (SPI mode) low and then high to re-start the device.

If Fault Mode is disabled (in GPIO mode, FLT_MODE pin = 1; in SPI mode, FLT_MODE bit = 1), no action is taken by the IC. The fault condition is reported, but does not affect the charge pump operation or switch states




Figure 10. Flowchart for Fault

Notes:

1. The un-faulted supply continues to be monitored when a fault occurs. The FLT signal remains faulted until both supplies are above their brownout trip level.
2. VDD_IO is not monitored unless it is connected to VDD.
3. VPP is not monitored if: VPPCOMP = 1 in SPI mode OR the CP_EN pin is low In GPIO mode.

External Circuitry

The MM101 internal driver requires external circuitry to operate its charge pump. The diagram below shows the suggested bypass capacitors that have been used with good results. Menlo Micro recommends selecting components with equal or better performance




Figure 11. MM101 Application Diagram

QFN Package Drawing

The 5 mm x 5 mm 32P QFN package drawing is below.




Figure 12. QFN Package Drawing

Footprint Details

Dimensions are given in millimeters.




Figure 13. QFN Footprint Drawing

Flip Chip Package Drawing

The 2.37 mm x 1.58 mm WLCSP Flip Chip package drawing is below.




Table 9. Flip-chip SOLDER BALL Locations

Ball #	Signal Name	X (um)	Y (um)	Ball #	Signal Name	X (um)	Y (um)	Ball #	Signal Name	X (um)	Y (um)
1	VDD	-990	458	12	FLIP_BIT	550	146	23	NC	990	-572
2	HV0	-770	458	13	FLIP_BIT	330	146	24	AGND	770	-572
3	HV1	-550	458	14	VPP	-330	146	25	FLTB	550	-572
4	HV2	-330	458	15	VPP	-550	146	26	NC	330	-572
5	HV3	-110	458	16	MISO / CTL3	-880	252	27	VDD_IO	110	-572
6	HV4	110	458	17	CP_EN	-880	-366	28	MODE	-110	-572
7	HV5	330	458	18	DGND	-550	-260	29	SSB / CTL4	-330	-572
8	HV6	550	458	19	DGND	-330	-260	30	MOSI / CTL2	-550	-572
9	HV7	770	458	20	VDD	330	-260	31	SCK / CTL1	-770	-572
10	VIN	990	458	21	VDD	550	-260	32	NC	-990	-572
11	CPGND	880	252	22	FLT_MODE	880	-366	—	—	—	—

X-Y position = Ball center with respect to Die Center

Bump Diameter = 100um to 105um

Bump Height = 80um

Recommended PCB Layout and SMT Parameters

For MM101-02ADA, non-solder mask defined pads are recommended. See [Figure 13](#) on page 27.

[Figure 14](#) below shows an example layout for the MM101 with supporting components.




Figure 14. Example PCB Layout

Symbol	Ref Des	Manufacturer	Part Number
C _{IN} , C _{DD_IO} , C _{DD}	C4, C6, C7	Samsung	CL10A105KA8NNNC
C _{PP}	C5	KEMET	C0603Y472K2RAC7867
R _{FLT}	R12	Yageo	RC0402FR-0749K9P

Recommended Solder Reflow Profile




Figure 15. Reflow Profile

Reflow profiles and assembly guidelines are given for RoHS-compliant (lead-free) solder alloy.

Follow Moisture Sensitivity Level (MSL) 3 handling precautions specified in IPC/JEDEC J-STD-020.


Storage and Shelf Life

Under typical industry storage conditions (≤30 °C/60% RH) in Moisture Barrier Bags:

- Customer Shelf Life: 24 months from customer receipt date
- Extended Shelf Life: 60 months from customer receipt date if re-bagged every 24 months or less.

Package Marking Information

The MM101 package marking and nomenclature are illustrated in [Figure 16](#).



Dot • = Pin 1 Indicator
Line 1 = 2D Bar Code
Line 2 = Human-readable product code

Figure 16. Package Marking Drawing

Package Materials Information




Figure 17. Tape and Reel Drawing

Package Options and Ordering Information

All Menlo Micro solutions are EAR99 compliant.

Part Number	Package Description	Temp Range	Device Marking ¹
MM101-02ADA	8ch charge pump driver IC - QFN	-40°C to +125°C	FAxxxxx
MM101-02ADA-TR	8ch charge pump driver IC – QFN, Tape and Reel (Qty 250)	-40°C to +125°C	FAxxxxx
MM101-03ADA	8ch charge pump driver IC - WLCSP	-40°C to +125°C	FAxxxxx
MM101-03ADA-TR	8ch charge pump driver IC – WLCSP, Tape and Reel (Qty 250)	-40°C to +125°C	FAxxxxx
MM101EVK1	Evaluation board for MM101 8ch charge pump driver IC - QFN		

Notes:

1. Additional markings may be present, including logo or lot trace code information. This information may be a 2D barcode or other human-readable markings. Note that 'x' is place holder for 5-digit numerical code.

Important Information

Disclaimer

The data presented in this document is for informational purposes only and shall in no event be regarded as a guarantee of conditions or characteristics. Any warranty or license for this product shall be specified and governed by the terms of a separate purchase agreement. Menlo Micro does not assume any liability arising out of the application or use of this product; neither does it convey any license under its patent rights, nor the rights of others.

Menlo Micro reserves the right to make changes in these specifications and features shown herein to improve reliability, function, and design; or to discontinue this product at any time without notice or obligation. Contact our product representative for the most current information.

Warning

This product is not authorized for use:

- In any life support systems.
- Applications for implanting into the human body, without the express written approval from Menlo Micro.

Trademark Notices

All trademarks and product service marks are owned by Menlo Microsystems, Inc.

Contact Information

Please contact Menlo Micro for the latest specifications, additional product information, test and evaluation boards, product samples, worldwide sales and distribution locations:

Internet: www.menlomicro.com

E-mail: sales@menlomicro.com

For product technical questions and application information: support@menlomicro.com.