



## SCHRACK FORCE GUIDED RELAYS SR6 NEXT GENERATION

TE Connectivity (TE) introduces SCHRACK force guided relays SR6 next generation. The SR6nG is a fully compatible successor of TE's force guided relay series SR6A/B/C/V/D/M. With its force guided contacts the state of a contact can be monitored with a diagnostic coverage of 99% (IEC 61508-2) which makes the SR6nG ideal to design safety circuits. The minimum contact load of 5V / 1mA allows direct monitoring through controller input. A more sensitive monostable magnetic coil system reduces heat generation. The relay height of 15.7mm fits best in 22.5mm DIN rail housings.

### BENEFIT

- Force guided contacts monitor the state of a contact with a diagnostic coverage of 99% (IEC 61508-2) which makes them ideal to design safety circuits
- Contacts are insensitive to voltage peaks and withstand even short-circuit currents up to 450A
- Relay height of 15.7mm for best fit in 22.5mm DIN rail housing
- Minimum contact load of 5V/1mA allows direct monitoring through controller input
- Sensitive monostable magnetic coil system to reduce heat generation

### KEY FEATURES

- Monostable relay with 6 (4) force guided contacts acc. to IEC 61810-3
- Circuits of up to 400V can be connected. Contacts can switch up to 8A or 2200VA
- Creepage and clearance distances allow reinforced isolation (IEC EN 62477) not just between coil and contacts but also between all contacts
- 6 pole version with 3 different contact sets (3NO/3NC; 4NO/2NC; 5NO/1NC)
- Special 4 pole version offers >15mm isolation between contacts
- Sensitive coil of 700mW allows use at 85°C under IEC 61810 conditions

## SCHRACK Force Guided Relays SR6 Next Generation

### APPLICATIONS

- Safety relay modules
- Safety controllers, PLC's
- Machines, presses, robots
- Emergency shut-off, light barriers
- Elevator and escalator safety control
- Railway level crossings, signaling

### ELECTRICAL

- IEC 60947-4-1: AC1-8A/250V 100k cycles @85°C
- EN 60947-5-1: AC15-5A/230V; DC13-6A/24V (NO)
- UL 61810: 8A GP, B300; R300 @85°C

### PART NUMBER LIST

Product code	Type	Contact arrangement	Contact material	Coil	Coil power	TE pn
SR6-423-L024	6 pole	4NO + 2NC	AgSnO <sub>2</sub> + Au flash	24VDC	700 mW	<a href="#">1558737-8</a>
SR6-336-L012		3NO + 3NC		12VDC		<a href="#">2-1558736-4</a>
SR6-336-L021		3NO + 3NC		21VDC		<a href="#">2-1558736-7</a>
SR6-336-L024		3NO + 3NC		24VDC		<a href="#">2-1558736-8</a>
SR6-426-L012		4NO + 2NC		12VDC		<a href="#">2-1558737-4</a>
SR6-426-L018		4NO + 2NC		18VDC		<a href="#">2-1558737-6</a>
SR6-426-L021		4NO + 2NC		21VDC		<a href="#">2-1558737-7</a>
SR6-426-L024		4NO + 2NC		24VDC		<a href="#">2-1558737-8</a>
SR6-426-L018-0V		4NO + 2NC		18VDC		<a href="#">2-1558739-6</a>
SR6-516-L012		5NO + 1NC		12VDC		<a href="#">2-1558738-4</a>

[te.com](http://te.com)

© 2023 TE Connectivity. All Rights Reserved.

TE Connectivity, TE connectivity (logo) and Every Connection Counts are trademarks owned or licensed by TE Connectivity. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

02/23 AK